



60° V-PORT CV CHART			
%	DN15	DN20	DN25
0%	0.00	0.00	0.00
10%	0.05	0.08	0.09
20%	0.28	0.35	0.68
30%	0.73	0.93	1.74
40%	1.11	1.46	2.78
50%	1.83	2.42	5.13
60%	2.92	3.85	8.00
70%	4.29	5.64	11.88
80%	7.00	9.21	18.71
90%	9.43	12.41	23.22
100%	12.78	16.28	32.84

SIZE	RATING	A	B	E BSP (F)
DN15 (1/2")	#400	60	31.8	1/2"
DN20 (3/4")	#400	72	40.5	3/4"
DN25 (1")	#400	89.5	48.7	1"

6	CABLE GLAND	02	1 x M20 x 1.5 & 1 x M16 x 1.5	LAPP KABEL
5	DIN/ISO 5211 PLATE	01	SS304	PEREGRINE
4	COUPLING	01	SS410	PEREGRINE
3	ACTUATOR MOUNTING STUD	02	M.S, NICKLE/CHROME PLATED	PEREGRINE
2	ELECTRIC ACTUATOR	01	ERQT 1530, 230VAC / 0(4)-20mA	PEREGRINE
1	SCREWED END V-PORT VALVE	01	CF8/SS304/RPTFE/#400/BSPT(F)	PEREGRINE
SR. NO.	ITEM DESCRIPTION	QTY.	MODEL / MATERIAL	MAKE
BILL OF MATERIAL				

NR	NEW RELEASE			DATE	SIGN.
MOD.NO.	REF.	MODIFICATION		DATE	SIGN.
MATERIAL : AS MENTIONED IN BOM			CLASSIFICATION OF CHARACTERISTICS CRITICAL..... ● KEY INSTRUCTION.....▲ MAJOR..... ● MINOR.....NONE	DRN.	26.03.2016 DJD
TREATMENT : -			DO NOT SCALE THE DWG. IF IN DOUBT ASK	CHD.	31.03.2016 SBS
* THIS DRAWING IS THE PROPERTY OF M/s. PEREGRINE TECHNOLOGIES PVT. LTD. & MUST BE RETURNED ON REQUEST. THIS IS FURNISHED AS CONFIDENTIAL INFORMATION & MUST NOT BE USED/COPIED OR LENT ANY PURPOSE WITHOUT OUR AUTHORITY IN WRITING.			CUSTOMER'S NAME : WESMAN THERMAL ENGINEERING PROCESSES PVT. LTD.	APPD.	31.03.2016 SBS
			TITLE: G. A. DRAWING OF MOTORISED 'V' PORT VALVE WITH SCREWED ENDS	ALL DIMENSIONS ARE IN MM	
			DRG.No. 164050E2230203	QTY. -	WT.(kg)-
			MODEL:	SCALE : NTS	
				SIZE	A4 MOD.NO. NR